



GSM/3G Home Alarm

Professional OEM/ODM Service

1. GSM Home/Office/Commercial Alarm System:

The S100, S110, S120 are new modules for GSM home alarm system with LCD display
 The S3523, S3526, S3524A are low cost for GSM home alarm system

Siemens TC35i GSM Engine Inside



S3523

Siemens TC35i GSM Engine Inside



S3526(*Hot sale)



S100(*Popular)

Android App



S110(*Top-rated)

Hot!



S120(*Metal case)

NEW

Model	Wireless zone	Wired zone	Relay out	Setup Model	SMS Alarm	Dialing alarm	LCD Display	Siren	Wireless Frequency	2 way Communication	Battery inside
S3523	8	2	1	SMS	3 numbers	5 numbers	/	Yes	433.92	/	Yes
S3526	8	2	1	SMS	3 numbers	5 numbers	/	Yes	433.92	/	Yes
S3524A	16	/	/	Keyboard	3 numbers	5 numbers	Yes	Yes	433.92	Yes/Handset	Yes
S100	16	/	2	Keyboard	3 numbers	5 numbers	Yes	Yes	433.92	Yes	Yes
S110	16	8	2	Keyboard	3 numbers	5 numbers	Yes	Yes	433.92	Yes	Yes
S120	16	20	2	Keyboard	3 numbers	5 numbers	Yes	Yes	433.92	Yes	Yes

2. Elderly Guarder/Emergency Call/Medical Alert:

A10/A11 special for safeguard and medical and including spiritual care for the elderly living, kids monitoring, disabled helping and home safety.

BIG RED PANIC BUTTON for emergency help calling

3 Familiarity Numbers Easy To Dial

4 times reminding take medicine

Wireless Smoke, Gas, Water leak sensors

Configuration by PC software via USB

Li-ion battery inside

*A11 support wireless siren

GSM Qua-band

Thoughtfulness design

Unique wireless water-proof and mistake-operation-proof Panic buttons



3. 3G Video Alarm Camera:

G310 is a newest camera can make video phone call when alarm via 3G network
 G320 support 3G network and WIFI, real-time monitoring on line(web or App)
 and make video phone call when alarm via 3G network.

Model	3G	WiFi	RJ45	USB	Server	Setup	Install	Wire-less zone	Alarm video call	Monitor online	Record	Review	App	Battery
G310	Yes	/	Yes	/	/	PC	indoor	Yes	Yes	None	Yes	/	/	Yes
G320	Yes	Yes	Yes	Yes	Yes	Web	indoor	Yes	Yes	Yes	H.264	Yes	Yes	/
G321	/	Yes	Yes	Yes	Yes	Web	indoor	Yes	/	Yes	H.264	Yes	Yes	/



G310



G320



G321



GSM/GPRS Industrial Controller and Monitoring System

4. GSM SMS Remote Controller Alarm & Telemetry RTU Automation:

S130,S140,S150 Special for Remote control and alarm, used for which require remote turning ON/OFF system, machines, and equipments remotely with a SMS from cell-phone therefore control & protect your assets. RTU5010,RTU5011 mainly used for remote alarm and control application based on GSM network. Such as pump,motor,generator,valve,oil pipe line, unmaned station, transformer, water well, etc. RTU5015 turn relay ON/OFF to OPEN/CLOSE door or gate or motors by phone call,2 NC/NO inputs for alarm. RTU5016 is a simple device for authorized temperature monitoring & remote control Air-Conditioner refrigeration storage.

Item\Model	S130	S140	S150	RTU5010	RTU5011	RTU5015	RTU5016
Digital Input	2	4	8	4	8	2	/
Relay output	2			4	8	1	2
Analog input	/			/	4(0-20mA)	/	1
USB	1			/			
RS232	/			1	1	/	/
SMS Alarm Numbers	3			10	10	2	5
Dialing Alarm Numbers	5			10	10	2/64*	/
Voice Call in	Yes*			/	Yes*	/	/
On-site Alarm	Yes*			Relay to siren		Yes*	/
AC Power failure alarm	SMS					/	SMS
Configurate	PC software(in standard package, Charge free)					SMS	SMS
Battery	Li-ion Rechargeable					/	Yes*
Adroid App	Yes			None		Yes	

Metal case, Small size, High efficiency and reliable performance,
*RTU5011 support internal temperature sensor. *Needs optional accessories
*RTU5015 has 64/up to 999(Customize) authorized number can call in to control the relay.



5. GPRS Data Logger--Remote monitor/control/log/manager system:

S200/S220/S240 Transmit and receive analog, digital and pulse counter data, PLC, Varity metering equipments to any device connected to the GSM/GPRS network such as mobile phones, Web Sites, monitoring center, control room, SCADA, etc.



Model	Analog input	Digital input	Temp. input	Relay output	USB	RS232	RS485	SCADA	Battery
S200	4	2	2	2	1	/	1	Support	Yes
S220	6	6	2	4	1	/	1	Support	Yes
S240	10	6	2	4	1	1	1	Support	Yes

6. GPRS Outdoor Alarm System S250:

An Economical and Practical Solution For Outdoor Electrical Power Unit(Transformer/Regulator) Protection. 8 digital inputs(NC/NO/EOL), 2 relay outputs (250V/10A,Tamper alarm). Display location map on web-based monitoring center(CMS-01 software) by GPRS network.



7. GPRS Temperature Logger:

Remote temperature monitor/log/report to cell phone by GSM SMS or transmitted real-time data to web-based monitoring center(CMS-02) S260 series used for refrigeration storage/Warehouse/Unmaned station or any temperature measurement needs.



Model	Best for	Temp. Sensor	Measurement range	Protocol
S260	General use	Semiconductor*1	-50~+120°C	GPRS
S261	Industrial use	Semiconductor*1	-50~+120°C	GPRS
S262		Semiconductor*2	-50~+120°C	Modbus TCP
S263		PT100*2	-50~+300°C	GPRS
S264		PT100*2	-50~+300°C	Modbus TCP